COMPLIANCE CONDITIONS OF File No J-11011/166/2011-IA-II (I) dated 21st November 2012.

Sub: Expansion from 3.0 MTPA to 5.0 MTPA Integrated Steel Plant along with installation of Pellet Plant - 4.0 MTPA and 300 MW Captive Power Plant at Geethapuram, Village Dolvi, Tehsil Pen, District Raigad in Maharashtra by M/s JSW Steel Limited.

Ref: Environmental Clearance for expansion of integrated steel plant from 3 to 5 MTPA vide letter No J-11011/166/2011-IA-II (I) dated 21st November 2012 & vide letter No J-11011/76/2013-IA II(I), dated July 30, 2015.

Sr. No.	ENVIRONMENTAL CLEARANCE CONDITIONS	COMPLIANCE STATUS
1	Waste gases from Blast furnace and coke ovens will be utilised for power generation. Fugitive emissions from raw material handling section will be suppresses by dry fogging system / water sprinkling.	 Complying with Waste Gas from Blast Furnace (BF) and Coke Oven Gas (COG) is used in 55 MW Captive Power Plant and other plants as fuel.
		 Gas Holders provided for storing the Coke Oven Gas, LD and BF Gases. Gas Holder will help the steady network flow for distribution of gas in constant pressure (Operating pressure 996 mmWC. Also it helps to proper utilization of waste gases. Total CO2 Savings will be approximately 660000 Ton of CO2 per year. Energy saving approximate 1 Million Gcal/Year. Total cost for both gas holders is Rs 86.97 (Rs 33.2 Crores + Rs 53.77 Crores)
		 De-dusting System with Bag filters at Junction houses of raw material handling section in Blast Furnace and Coke Oven Plants. De-dusting System with Bag filters at

Stock House - 2 Nos Cast house fume extraction system with Bag Filters

- Dust suppression by dry fog systems / water spraying systems provided at Raw Material Handling Section (RMHS) and other applicable areas.
- All conveyors and Junction houses of Raw Material Handling systems are closed system.
- Total Investment on Yard sprinklers, De-dusting system and Dry fogging system Rs 77.29 Crores

Details of covered shed for storage of Raw Material;

- Covered shed for Jetty yard-A with a capacity of 110,000MT for Coal Storage
- Covered shed for Jetty yard-B with a total capacity of 305,000 MT for Iron Ore and Flux.
- Covered Sheds (2 Nos) for Pellet and Coke Storage of Capacity-1,20,000 MT each.
- Covered shed for storing Iron Ore Bearing Material and Flux is in progress. Capacity 4,27,000 MT

Total expenditure on cover shed is approximately 320 Crores.

Environmental Benefits of Covered Shed:

- No fugitive emission during handling of material
- No water contamination during rains
- No spillage of material on roads
- Covered storage shed will prevent dust emission in the environment during operation of the yard.

To control the fugitive emissions in Coke Oven Plant, following Control Measures are provided;

• Bag Filters for coal crushing & mixing

station & route

- Ground De-dusting system with Bag Filters – connected to charging and pushing, primary crusher, coke cutter, secondary coke crusher area
- Bag Filters for coke screen house & Silo.
- Dust suppression system at all the transfer points, coal handling and coke handling route.

Hence the condition has been complied

Complying with

- The makeup water requirement for the proposed expansion is limited to 2590 m3/hr (inadvertently mentioned as m3/day) besides the existing consumption for 3 MTPA plant
- The water is sourced from the Nagothane dam at K.T. Bandhara as per the allocation from the Water Resources Department of Maharashtra.
- Treated waste water & cooling tower blow down (CTBD) are used for dust suppression, slag cooling & plantation. There is no waste water discharge form the plant.
- Sewage is treated in septic tanks & STPs & reused for gardening.
- Bag Filter dust is recycled & reused in the process of Sinter & Pellet Making.
- Blow down of power plant is used in SMS slag recovery plant for dust suppression.
- Blow down water from Blast furnace 1 recirculation system is reused in the slag granulation plant (SGP) as make up water to SGP recirculation water system.
- Treated water from Coke oven byproduct is used in coke quenching

Hence the condition has been complied

2 The makeup water requirement for the proposed expansion will be 2,590 m³/day and the existing consumption is 833.3 m3/day, which shall be sourced from the State Water Resources Dept. from Nagothane dam at K.T. Bandhara. Maximum recycling of wastewater will be done after treatment to achieve zero discharge. Treated wastewater will be used for dust suppression and green belt development. Effluent streams such as cooling tower blow down, floor washings etc. will be used for fugitive dust suppression, water sprinkling etc. Sewage will be treated in septic tanks. Bag filter dust will be recycled in the process. Blow down water from power plant will be reused in steel melting shop slag yards for spraying on hot slag. down water from Blast furnace recirculation system will be reused in the slag granulation plant as make up water to SGP recirculation water system. Treated waste water from coke oven by products plant will be used in the system itself.

3	BF slag will be granulated and used for cement manufacturing. Slag from SMS production will be used in the sinter plant, in land / road / area development or for manufacturing of insulated bricks etc. Mill scale, flue dust from the blast furnace, dust from the bag filters will be used in Sinter plant. All pumps and motors will be selected from less noise generating types. Ear plugs will be provided to employees working in high noise prone areas. DG set will be provided with silencer.	 100% granulated slag of Blast furnace - 1 is used in Cement Plant for making of Cement in JSW Group Company. SMS- EAF slag is used in the sinter plant, in internal roads / land reclamation, area and construction of concrete structures and road construction in National Highways. Mill scale, flue dust from Blast Furnace 1, dust from Bag Filters used in Sinter plant. GCP dust from SMS 1 is used in Sinter Plant and Pellet plant Low noise level pumps and motors are used. Ear plugs / Ear muffs provided to all employees working in high noise prone areas. DG sets having provided with silencer. Hence the condition has been complied
4	All the integrated steel plant are listed as S. No 3 (a) as Primary Metallurgy Industries under category A of the Schedule of EIA Notification 2006 and appraised by the Expert Appraisal Committee (Industry-I) of MoEF.	Complying with As per the EIA Notification 2006 and as per the EC conditions stipulated by MoEFCC for integrated steel plant listed as S.No 3 (a) as Primary Metallurgy Industries under category A
5	The proposal was considered by the expert Appraisal Committee -1 (industry) in its 37 th Meeting held during 14 th and 15 th June 2012. The Committee recommended the proposal for Environmental clearance subject to stipulation of specific conditions along with other environmental conditions. Public hearing was conducted on 28.02.2012.	Industry is complying with all the general conditions and specific conditions stipulated in the Environment Clearance. Complied the points raised during Public Hearing.
6	Based on the information submitted by you, presentation made by you and consultant, M/s. MECON Limited., Ranchi, the Ministry of Environment and Forests hereby accords Environmental clearance to the above project under the provision of EIA Notification dated 14 th September 2006 subject to strict compliance of the following specific and general	Industry is complying the general conditions and specific conditions stipulated in the Environment Clearance under the provision of EIA Notification 2006.

conditions.

Specific Conditions;

i Measures shall be undertaken to mitigate particulate levels in the ambient air and a time bound action plans shall be submitted. On-line ambient air quality monitoring with proper O&M and continuous stack monitoring facilities for all the process stacks shall be provided and sufficient air pollution control devices viz. Electrostatic precipitator (ESP), gas cleaning plant, scrubber, bag filters etc. shall be provided to keep the emission levels below 50 mg/Nm3 by installing energy efficient technology.

Complied

- Adequate dust control measures (Bag filters, ESPs, Venturi Scrubbers, Cyclones) have been provided to all the units to mitigate particulate levels in the ambient air quality. Environmental monitoring parameters are well within the prescribed standards as per the Consent granted by MPCB.
- Five Continuous Ambient Air Quality Monitoring stations have been installed in consultation with MPCB. All these stations are connected to URL of MPCB & CPCB & data is being transmitted online on real time basis for PM2.5, PM10, SO2, NOx & CO with proper O&M
- Continuous Stack Emission Monitoring systems are installed at all major stacks (Process stacks) & connected to URL of MPCB & CPCB & data is being transmitted online on real time basis.
- Electrostatic precipitator (ESPs), gas cleaning plants, scrubbers, bag filters etc. are provided to all units & PM levels are well within the prescribed norms as per MPCB Consent conditions.
- ii As proposed, Electrostatic precipitator (ESP) shall be provided to sinter / Pellet plant, WHRB, DE Plants and dust catcher followed by venturi scrubbers to blast furnace to control SPM levels within 50 mg/Nm3. Fume extraction system shall be provided to induction furnaces to control the emissions within the prescribed standards.
- Electrostatic precipitator provided in Blast Furnace 1, Sinter Plants & Pellet plant,
- Cast House Fume Extraction System, Waste Heat Recovery Boiler (WHRB), Dust Extraction System and dust catcher followed by venturi scrubbers, de-dusting system with bag filters in stock houses in Blast Furnace are provided.
- The emission level from the stacks are well within the prescribed standards.
 The Copy of the Six Monthly Stack Emission Monitoring Report is attached

		herewith in Annexure 1
		• JSW Steel Ltd., Dolvi, there is no Induction Furnace installed, however in Steel Melting Shop 1, Electric Arc Furnace (EAF) connected with - Gas Cleaning Plants (4 Nos) with bag filters provided with primary and secondary fume extraction systems. The emission level is well within the prescribed standards. The existing Gas Cleaning plants (GCPs 1, 2 &3) were modified and the guaranteed parameters of PM level in stacks are < 50 Mg/Nm3.
		Hence the point is being complied
iii	The National Ambient Air Quality Standards issued by the Ministry vide G.S.R. No. 826 (E) dated 16th November, 2009 shall be followed.	On line Ambient air quality monitoring system (5 Nos) installed in the plant for the parameters PM10, PM2.5, SO2, NOx, CO and the data is uploaded in the CPCB and MPCB servers.
iv	Gaseous emission levels including secondary fugitive emissions from all the sources shall be controlled within the latest permissible limits issued by the Ministry and regularly monitored. Guidelines/Code of Practice issued by the CPCB shall be followed. New standards for the sponge iron plant issued by the Ministry vide G.S.R. 414 (E) dated 30th May, 2008 should be followed.	 Complying with Adequate measures have been taken to control the gaseous emission levels. Secondary fugitive emissions at Blast Furnace 1 - Cast House de-dusting system with Bag filters, Stock House de-dusting system with Bag filters. Gas Cleaning Plants (4 Nos) for Electric Arc Furnace (EAF) of Steel Melting Shop (SMS – 1) from all the sources and are well within the permissible limits issued by the Ministry and regularly monitored. A new standard for the sponge iron plant issued by the Ministry vide G.S.R. 414(E) dated 30th May, 2008 is being followed. As per the new guidelines of Sponge Iron Plant, the monitoring for stack emissions, work place monitoring etc. are carried out and the reports are within the CPCB

		norms.
V	Total makeup water requirement for expansion shall not exceed 2,590 KLD. Efforts shall further be made to use maximum water from the rain water harvesting sources. Use of air cooled condensers shall be explored and closed circuit cooling system shall be provided to reduce water consumption and water requirement shall be modified accordingly. All the effluent should be treated and used for ash handling, dust suppression and green belt development. No effluent shall be discharged and 'zero' discharge shall be adopted. Sanitary sewage should be treated in septic tank followed by soak pit.	 Complying with The makeup water requirement for the proposed expansion is within the water allocated and less than 2590 m3/hr. Roof Top Rain water harvesting system have been implemented. Closed circuit cooling towers are provided to optimize water consumption. All effluent is treated & recycled in the process and reused in slag cooling, dust suppression & plantation purpose. No waste water is discharged to outside the plant premises except run off during monsoon. Septic tank followed by soak pits provided in all plant areas. Sewage Treatment Plants (STP) 3 Nos provided for treatment of sewage. The treated sewage water is used for gardening.
vi	Efforts shall be made to make use of rain water harvested. If needed, capacity of the reservoir should be enhanced to meet the maximum water requirement. Only balance water requirement shall be met from other sources.	 Complying with Roof top Rain water harvesting system has been established (at 12 various buildings of Oxygen Plant, Coke Oven, Power Plant, MRSS and Admin.) The harvested rain water is being used in the cooling towers as make up water. Since the water table is very high, therefore recharging ground water table is not feasible.
vii	Regular monitoring of influent and effluent surface, sub-surface and ground water (including chromite) should be ensured and treated wastewater should meet the norms prescribed by the State Pollution Control Board or described under the E (P) Act whichever are more stringent. Leachate study for the effluent generated and analysis shall also be regularly carried out and report submitted to the Ministry's Regional Office at Bhopal, SPCB and	Regular monitoring of influent and effluent surface, sub-surface is being done by MoEFCC approved and NABL accredited labs & the results of all parameters are well within the prescribed standards. The plant is not using any ground water. Analysis reports are submitted to the

	СРСВ.	Regional Office, MoEF&CC, MPCB & CPCB on regular basis. All monitoring reports are submitted as
		per guidelines to;MPCB - Once in three months, also as & when required,
		 MOEF&CC, Nagpur & Delhi – Once in Six month, CPCB, New Delhi – Monthly basis
viii	The water consumption shall not exceed as per the standard prescribed for the steel plants.	Water consumption is well within the prescribed norms & CREP guidelines for the steel plants (less than 5 m3/ton of crude steel)
		Specific water consumption for the steel plant for 2023-24 (up to March 2024) is 2.49 M3/TCS
		Hence the point is being complied
ix	Vehicle pollution due to transportation of raw material and finished products shall be controlled. Proper arrangements shall also be made to control dust emissions during loading and unloading of the raw material and finished product.	 Transportation of raw material is mainly through sea route to captive jetty and further to the steel plant via closed conveyors. Rs 320 Crores have been spent for covered shed for storage of raw material like coal, Iron Ore and Flux at Jetty & Raw Material storage yard to control the dust emission. Transportation of finished products is mainly by rail. Adequate dust suppression systems have been provided to control dust emissions during loading and unloading of the raw material and finished product. Dust Suppression such as; Dry Fog System / Water spraying in junction houses / Transfer Towers at Raw Material Handling System (RMHS) & other
		units All the Junction houses and Conveyors are covered to avoid fugitive emissions while transfer of material through conveyor.

Х	All internal roads shall be black topped. The	Complying with
	roads shall be regularly cleaned with mechanical sweepers. A 3 tier avenue plantation using	All internal roads are concreted &
	native species shall be developed along the	Vacuum based road sweeping
	roads.	machines (6 Nos) and mist type mobile
		water tankers (2 Nos) are provided for
		control of road emissions.
		Avenue plantation using native species
		have been planted along the roads.
xi	Proper handling, storage, utilization and disposal	Complying with
	of all the solid waste shall be ensured and	
	regular report regarding toxic metal content in	Proper handling, storage, utilization and
	the waste material and its composition, end use of Solid/hazardous waste should be submitted	disposal of all the solid wastes like Iron ore fines, coke fines, fluxes and scales
	to the Ministry's Regional Office at Bhopal, SPCB	generated from the plant is used in Sinter
	and CPCB.	Plants & Pellet Plant. Material have been
		shifted through conveyor, closed bulkers
		and loaded by pneumatic conveying
		system.
		The report of Solid wastes and Hazardous
		wastes generation and disposal are
		regularly submitted as mentioned below.
		MPCB - Once in three months, also as
		& when required,
		 MOEF&CC, Nagpur & Delhi – Once in Six month,
		CPCB, New Delhi – on Monthly Basis.
xii	Proper embankment shall be provided for the sludge disposal area.	Complying with
	strage disposar area.	Proper embankment provided to
		contain sludge at all generating points-
		Sponge Iron Plant, Blast Furnace 1 and
		Hot Strip Mill 1.
		Sludge generated from the Effluent treatment plants (Spange Iron Blant)
		treatment plants (Sponge Iron Plant, Blast Furnace, are used in sinter making
		& Pelletization process.
		In sludge handling areas filter press and
		vacuum drum filters installed at Sponge
		Iron Plant, Hot Strip Mill and Blast
		Furnace.

xiii	Risk and Disaster Management Plan along with	Risk and Disaster Management plan is
7	the mitigation measures shall be prepared and a copy submitted to the Ministry's Regional Office at Bhopal, SPCB and CPCB within 3 months of issue of environment clearance letter.	prepared and has been already submitted to MoEF&CC along with EIA Report
xiv	As proposed, green belt shall be developed in 33 % of plant area as per the CPCB guidelines in consultation with the DFO.	Green belt is being developed as per the further amendment in EC obtained dtd 16.06.2020.
		Green Belt within Plant:
		Presently, 13% green belt is developed over 18.00 ha land within the plant premises with 2,11,388 nos of trees. Balance 18.42 Ha (3%) green belt area is to being developed with 46,200 nos of trees. Green belt developed with tree density 2500 trees/hectare and local species.
		Green Belt Outside Plant in 10 Km area:
		Green belt outside the plant premises has been developed over 203.00 Ha i.e. 33 % as per EC. Green belt outside the plant premises is developed in forest land in proximity of the plant area in consultation with local forest department over 51 Ha land and Mangrove Plantation over 152.00 Ha.
		Hence, Condition is complied.
XV	All the recommendations made in the Charter on Corporate Responsibility for Environment Protection (CREP) for the Steel Plants should be implemented.	Complying with The recommendations made in the Charter on Corporate Responsibility for Environment Protection (CREP) for the steel plants are implemented.
		 Coke oven plant – Tar sludge / ETP sludge are reused in the Coking process. Blast Furnace – Energy recovery of top blast furnace gas is being done with power generation through TRT by using top pressure of BF gas. Coke Oven Plant - Coke Dry Quenching

- systems (3 Nos) (CDQ) installed and recover the sensible heat of red hot coke, reduce energy consumption and pollution and improve the quality of coke. Each CDQ will reduce water consumption by 1920 m3/day and energy of 70 MW will be recovered along which will reduce the CO2 emissions by approx. 10.9 Lac.t CO2eq
- Steel Melting Shop (SMS), secondary de-dusting system (Gas Cleaning Plants 4 Nos) has been installed to control fugitive emissions
- Coal Injection Plant for direct injection of pulverized coal in furnace has been implemented. Present rate of CDI in our Blast Furnace is 200 Kg/THM (average for the year 2023-24).
- Blast Furnace Slag (BF) Slag- 100% utilized in Cement plant.
- Electric Arc Furnace Slag (EAF) slag-100 % for construction activities, land filling in the low lying areas of expansion projects and is also being used for internal road making and Concrete and asphalt roads.
- Presently Steel slag is used as aggregates for construction roads in National Highways with coordination with Central Road Research institute (CRRI), New Delhi.
- Cast House Fume extraction system inclusive of tap holes, runners, skimmers, ladle and charging points have been provided to control Fugitive emissions from Blast Furnace.
- The specific water consumption for the year 2023 – 24 (April to March 2024) was 2.49 m3/t of crude steel which is well below the targets for flat products and as well as for long products.
- Online Stack Monitoring System

		have been installed on all major stacks (33 Nos) and 5 Nos Online Ambient Air Quality Monitoring System. The real time data is interlinked with MPCB and CPCB server.
xvi	The company shall adopt well laid down corporate environment policy and identified and designate responsible officers at all levels of its hierarchy for ensuring adherence to the policy and compliance with environmental clearance, environmental laws and regulations.	Complied Environment Policy is in place and being complied in adherence to Environmental Clearance, Environmental Laws and Rules and Regulations.
xvii	All the commitments made to the public during the Public Hearing / Public Consultation meeting held on 28th February, 2012 should be satisfactorily implemented and a separate budget for implementing the same should be allocated and information submitted to the Ministry's Regional Office at Bhopal.	Complying with The commitments made to the public during the Public Hearing / Public Consultation meeting held on 28th February, 2012 is being implemented and a separate budget is maintained for implementing the projects/ issues under CSR activities. In 2023-24 the industry has spent Rs 13.42 crores on CSR activities. Following are the activities carried out in 2023-24: Education: UDAAN Scholarship, School Infrastructure Development and ASPIRE — Life Skills Distribution of School Infrastructure and skills enhancement: JSW UDAAN Scholarship: JSW UDAAN Scholarship: JSW ASPIRE Project:
		Health & Nutrition: Adolescents Health & MCH Program, Care & Support to Migrating Population, Vision Care, Community Health Camps. Under this scheme JSW Steel is doing Quality & affordable healthcare services and Maternal & Child Health Care and Non Communicable diseases Control &

rehabilitation of differently able. Health & Wellness initiatives taken at Sanjeevani Hospital: • The hospital covers 4.5 Acres Land and provided 73 BEDS and 10 OPDS with ICU, PICU and NICU, Maternal & Child Health Care The facilities with services available in the Sanjeevani hospital is provided Intellectual Disability, Eye Care Services, Heart Surgeries, CT SCAN, USG, ECHO, X RAY, Knee replacement **Community Development:** Development of Rural Infrastructure and Linkage with Livelihood, Community Care, Road & Domestic Safety, Pathways & Roads, Community Halls Illumination and Govt. Schemes convergence. 15 Gram panchayats, 33 villages and more than 52000 peoples benefitted though this activities. Constructed 12 Community Buildings and 8 KM Road & Pathways in the nearby villages. Natural Resource Management: Water Projects: Drinking & Domestic and Mangrove restorations Water, Environment & Sanitation scheme provided the Water Resource through laying of pipelines at 33 villages. Provision of HDPE tanks, Roof rain water harvesting systems, Community Ponds, Pipelines, Elevated storage reservoir, Ground water reservoir, Check Dams, Bunds, Filtration units. At least 5 % of the total cost of the project **Complying with** xviii should be earmarked towards the Enterprise Social Commitment based on Public Hearing CSR activities in various sectors are being issues and item-wise details along with time done in the surrounding villages and a

	bound action plan should be prepared and submitted to the Ministry's Regional Office at Bhopal. Implementation of such program should be ensured accordingly in a time bound manner.	time bound action plan for various CSR activities have been submitted to MoEF&CC as per EAC recommendation of 2.5% of project cost. Amount spent on CSR Activities: For 2023-23 (April to March 2023): Rs 13.42 Crores. The above amount has been spent on Social Development- (Education & Training), Skill Development, Water and Sanitization, Agriculture, Rural Development, Health, Solid Waste Management and Community Development.
xix	The company shall provide housing for construction labour within the site with all necessary Infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STP, safe drinking water, medical health care, crèche etc. The housing may be in the form of temporary structures to be removed after the completion of the project.	Industry has Complied the conditions during installation and commissioning of the plant. Provided housing for labour within the site with all necessary Infrastructure and facilities such as fuel for cooking, mobile toilets, mobile STPs, safe drinking water, medical health care, crèche etc. After completion of the project activities the temporary structures have been dismantled and removed.
Gene	ral Conditions:	
i	The project authorities must strictly adhere to the stipulations made by the Maharashtra State Pollution Control Board and the state government.	Complied All the terms & conditions stipulated by Maharashtra Pollution Control Board (MPCB) and State Government are being followed.
ii	No further expansion or modification in the plant shall be carried out without prior approval of the ministry of Environment and Forests.	Complied As per the EC conditions, expansion or modifications of the plant was done. Industry has done in all expansion activities after obtaining prior Environmental Clearance from MoEF&CC.
iii	The gaseous emission from various process units shall conform to the load/mass based standards notified by this ministry on 19 th may, 1993 and	Adequate Air Pollution Control measures have been provided to each unit of the plant and the Gaseous emissions from

standards prescribed from time to time. The the process units are well within the State Boards may specify more stringent prescribed standards as notified by the standards for the relevant parameters keeping in Ministry. view the nature of the industry and its size and Complied the Consent conditions as per location. the Maharashtra Pollution Control Board under The Air Act, The Water Act and Hazardous Waste Management & handling and Transboundary Rules. Hence the point is being Complied ίV At least four ambient monitoring stations should **Complying with** be established in the downward direction as well • Five Continuous Ambient Air Quality as where maximum ground level concentration Monitoring stations have of PM10, SO2 and NOx are anticipated in installed in consultation with MPCB. All consultation with the SPCB. Data on ambient air these stations are connected to URL of quality and stack emission shall be regularly MPCB & CPCB & data is being submitted to this ministry including its regional transmitted online on real time basis office at Bhopal and the SPCB/CPCB ones six for PM2.5, PM10, SO2, NOx & CO. months. • 33 Nos. Continuous Stack Emission Monitoring systems for plants under 5 MTPA (Phase I) are installed at all major stacks & connected to URL of MPCB & CPCB & data is being transmitted online on real time basis. Data on Stack Emission, Ambient Air Quality and Work Environment Air Quality are being submitted to; MPCB - Once in three months, MOEF&CC, Nagpur & Delhi – Once in Six month, CPCB, New Delhi – Monthly basis Hence the point is being Complied. Industrial Waste water generated from Industrial wastewater shall be properly collected, treated so as to conform to the standards the plant is treated in the plants and prescribed under GSR 422 (E) dated 19th may, reused in the process/ slag cooling 1993 and 31st December, 1993 or as amended purpose. from time to time. The treated wastewater shall be utilised for plantation purpose. There is no discharge of industrial waste water to outside the plant premises. Hence the point is being Complied

Vi	The overall noise level in and around the plant area shall be kept well within the standards (85 dBA) by providing noise control measures including acoustic hoods, silencers, enclosures etc. on all sources of noise generation. The ambient noise level should conform to the standards prescribed under EPA rules, 1989 viz. 75dBA (daytime) and 70 dBA (night time).	Noise control measures installed in the plants like acoustic hoods, silencers, enclosures etc. on all sources of noise generation & measured noise level are well with in prescribed standards. The ambient noise level is monitored in the boundary of the plant and the values are well within the standards prescribed under EPA rules, 1989 viz. 75dBA (daytime) & 70 dBA (night time). Hence the point is being Complied
vii	Occupational health surveillance of the workers should be done on a regular basis and records maintained as per the factory Act.	As per the Factories Act, regular health surveillance done for all the workers and employees & records are maintained on regular basis. Hence the point is being Complied
viii	The company shall develop surface water harvesting structure to harvest the rain water for utilization in the lean season besides recharging the ground water table.	Roof top Rain water harvesting system is being implemented 12 buildings and the harvested rain water is being used in the cooling towers. Since the water table is very high, therefore recharging ground water table is not being done.
ix	The project proponent shall also comply with all the environmental protection measures and safeguards recommended in the EIA/EMP report. Further, the company must undertake socioeconomic development activities in the surrounding villages like community development programmes, drinking water supply and health care etc.	 Environmental protection measures & safeguards recommended in EIA/EMP report are being complied. Socio – economic development activities / programmes like supply of drinking water, health care camps & community development programmes, Self Help Groups, Training and education, Rural Development, Sanitary etc. are being carried out on regular basis and will be continued as per plan. Hence the point is being Complied.
х	Requisite amount shall be earmarked towards capital cost and recurring cost/annum for environment pollution controls measures to implement the conditions stipulated by the	Requisite amount is earmarked towards capital cost and recurring cost/annum for environment pollution controls measures to implement the conditions stipulated by

	ministry of environment and forest as well as the state Government. An implementation schedule for implementing all the conditions stipulated herein shall be submitted to the regional office of the ministry of the Bhopal. The funds so provided shall not be diverted for any other purpose.	the MoEF&CC as well as the State Government. The funds earmarked for Environmental pollution control measures are properly utilized. The funds earmarked is not diverted any other purpose.
хi	A copy of clearance letter shall be sent by the proponent to concerned Panchayat, Zila parishad /municipal corporation, Urban local body and the local NGO, if any, from whom suggestions / representations, if any, were received while processing the proposal. The clearance letter shall also be put on the web site of the company by the proponent.	Complied A copy of clearance letter is already submitted to concerned Panchayat, Zillah Parishad/Municipal Corporation, Urban Local Body and the local NGO. The Environment Clearance letter also put on the JSW Web site.
xii	The project proponent shall upload the status of compliance of the stipulated environment clearance conditions, including results of monitoring data on their website and shall update the same periodically. It shall simultaneously be sent to the regional office of the MOEF at Bhopal. The respective zonal office of the CPCB and the CECB. The criteria pollutant levels namely; PM10, SO2, NOx (ambient levels as well as stack emission) or critical sectoral parameters, indicated project shall be monitored and displayed at a convenient location near the main gate of the company in the public domain.	Complied. The status of compliance of the stipulated environment clearance conditions, including results of monitoring data on their website and shall update the same on six monthly basis. The EC compliance and Environmental monitoring reports are submitted to MoEFCC, CPCB. The CEMS data and CAAQMS data are displayed at the main gate.
xiii	The project proponent shall also submit six monthly reports on the status of compliance of the stipulated environmental conditions including results of monitored data (both in hard copies as well as by e-mail) to the regional office of MoEF, the respective Zonal office of CPCB and the SPCB. The Regional office of this Ministry at Bhopal / CPCB / SPCB shall monitor the stipulated conditions.	Being Complied. The six monthly Environmental Clearance compliance report and Environmental monitoring reports are submitted to Regional Office of MoEFCC, MPCB and CPCB.
xiv	The Environmental Statement for each financial year ending 31 st March in Form V as is mandated to be submitted by the project proponent to the concerned State Pollution Control Board as	Being submitted regularly Plant wise Environment Statement for 2021-22 prepared and submitted to

	prescribed under the Environment (Protection) Rules 1986, as amended subsequently, shall also be put on the website of the company along with the status of compliance conditions and shall also be sent to the respective Regional Office of	MPCB portal and uploaded on the web site of the company. Also the same are submitted to regional office of MoEFCC along with six monthly EC compliance report.
	the MoEF at Bhopal by e-mail.	
xv	The project proponent shall inform the public that the project has been accorded environmental clearance by the Ministry and copies of the clearance letter are available with the SPCB and may also be seen at Website of the Ministry of Environment and Forests at http/moef.nic.in. This shall be advertised within seven days from the date of issue of the clearance letter, at least in two local newspapers that are widely circulated in the region of which one shall be in the vernacular language of the locally concerned and a copy of the same should be forwarded to the Regional Office, Bhopal.	Published in newspaper as per guidelines namely in Local newspaper Dainik Krushiwal, Raigad Times, Ramprahar dated 24/11/2012 and English newspaper Indian Express dated 26/11/2012. Hence this point is complied.
xvi	Project authorities shall inform the Regional Office as well as the Ministry, the date of financial closure and final approval of the project by the concerned authorities and the date of concerned authorities and the date of commencing the land development work.	Complied
11	The ministry may revoke or suspend the clearance, if implementation of any of the above conditions is not satisfactory.	Noted
12	The Ministry reserves the right to stipulate additional conditions if found necessary. The Company in a time bound manner shall implement these conditions.	Noted
13	The above conditions shall be enforced, inter-alia under the provisions of the Water (Prevention and Control of Pollution) Act 1974, the Air (Prevention and Control of Pollution) Act 1981, the Environment (Protection) Act 1986, Hazardous Wastes (Management, Handling and Transboundary Movement) Rules 2008 and the Public (Insurance) Liability Act 1991 along with their amendments and Rules.	 The plant is regularly complying for The water (Prevention& Control of Pollution) Act 1974, The Air (Prevention and Control of Pollution) Act, 1981 The Environment (Protection) Act 1986 The Public Liability Insurance Act, 1991 along with their amendments and rules.

Annexure 1


Stack Emissions Report

JSW STEEL LIMITED

Integrated Steel Mill Complex Geetapuram, Dolvi, Tal - Pen, Dist - Raigad

A) STACK EMISSION:

Hot Strip Mill Plant Cap Provided Cap C	Sr.	Sr. Name of the Plant and Stack	Stack connected to (Name of the Unit)	Height of the Stack	Diameter of the Stack	Pollution Control unit	Date & time of Monitoring	Production fig. of	Velocity m/sec	Paı	Parameters mg/Nm ³	mg/Nm ³	
Hot Strip Mill Plant CGP - 1 Stack SMS Furnace 70.5 5.5 Bag Filters 02/10/23 10/35 Hrs 10418.0 16.99 11 15.5 16.0				(m)	(m)	provided		the monitoring period (TPD and MWh)		Particulate Matter (PM)	SO ₂	NOx	8
GCP - I Stack SMS Furnace 70.5 5.5 Bag Filters Q2/10/23 10:35 Hrs 10418.0 16.99 11 15.0 16.0 GCP - I Stack SMS Furnace 70.5 5.5 Bag Filters Q2/10/23 10:35 Hrs 9937.0 17.68 10 14.0 18.0 GCP - II Stack SMS Furnace 70.5 5.5 Bag Filters Q2/10/23 12:30 Hrs 10/18.0 15.80 7 11.0 14.0 GCP - II Stack SMS Furnace 70.5 5.5 Bag Filters Q2/10/23 12:30 Hrs 10/18.0 14.58 5 12.0 GCP - III Stack SMS Furnace 66.5 3.3 Bag Filters Q2/10/23 12:30 Hrs 9937.0 16.45 5 25.0 16.0 GCP - III Stack SMS Furnace 66.5 3.3 Bag Filters Q2/10/23 12:30 Hrs 9937.0 16.45 5 25.0 16.0 GCP - III Stack SMS Furnace 66.5 3.3 Bag Filters Q2/10/23 12:30 Hrs 9937.0 16.0 17.0 17.0	-	Hot Strip Mill Plant					Plant Ca	spacity: 3.0 MT	PA				
1011/23 10.00 Hrs 95840 16.91 11 13.0 15.0	-	GCP - I Stack	SMS Furnace	70.5	5.5	Bag Filters	02/10/23 10:35 Hrs	10418.0	16.99	11	15.5	16.0	18.0
11/12/23 10.35 Hrs 99370 17.68 10 14.0 18.0							10/11/23 10:00 Hrs	9584.0	16.91	11	13.0	15.0	18.0
GCP-II Stack SMS Furnace 70.5 5.5 Bag Filters 01/01/24 10:15 Hrs 10164.0 16.23 11 15.0 12.0 GCP-II Stack SMS Furnace 70.5 5.5 Bag Filters 02/10/23 12:05 Hrs 100320 16.89 7 11.0 14.0 GCP-II Stack SMS Furnace 70.5 5.5 Bag Filters 02/10/23 12:05 Hrs 1001/24 12:10 Hrs 1645 9 15.0 <t< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td>11/12/23 10:35 Hrs</td><td>9937.0</td><td>17.68</td><td>10</td><td>14.0</td><td>18.0</td><td>28.0</td></t<>							11/12/23 10:35 Hrs	9937.0	17.68	10	14.0	18.0	28.0
GCP-II Stack SMS Furnace 70.5 5.5 Bag Filters 02/10/23 12:00 Hrs 10183.0 15.80 7 11.0 14.0 16.0 16.0 16.0 16.0 16.0 16.0 16.0 16							01/01/24 10:15 Hrs	10164.0	16.23	- 11	15.0	12.0	18.0
GCP-II Stack SMS Furnace 70.5 5.5 Bag Filters 02/10/23 12:05 Hrs 10030.0 16.05 7 18.0 16.0 GCP-II Stack SMS Furnace 70.5 5.5 Bag Filters 02/10/23 12:05 Hrs 9937.0 16.45 9 15.1 12.0 GCP-III Stack SMS Furnace 66.5 3.3 Bag Filters 02/10/24 12:30 Hrs 9536.0 17 4 13.0 16.0 Tunnel Furnace - I- A Stack Tunnel Furnace - I- A Stack Tunnel Furnace - I- A Stack 5.0 1.5 10.0 12.0							26/02/24 10:00 Hrs	10183.0	15.80	7	11.0	14.0	13.21
GCP - II Stack SMS Furnace 70.5 5.5 Bag Filters 02/10/23 12:05 Hrs 10418.0 14.95 9 15.1 12.0 GCP - II Stack SMS Furnace 66.5 3.3 Bag Filters 01/01/24 12:10 Hrs 10/18.3 15.45 4 13.0 16.0 GCP - III Stack SMS Furnace 66.5 3.3 Bag Filters 02/10/24 15:15 Hrs 10/18.3 8.76 6 14.0 18.0 Tunnel Furnace - I - A Stack Turnel Furnace - I - A Stack Turnel Furnace - I - A Stack 1.5 1.7 4 15.0 1.0 Account of Furnace - I - A Stack Turnel Furnace - I - A Stack Turnel Furnace - I - A Stack 1.5 1.1/12/23 16:50 Hrs 9937.0 6.01 6 1.0 1.0 1.2 Account of Furnace - I - A Stack Turnel Furnace - I - A Stack Turnel Furnace - I - A Stack 1.5 1.1/12/23 16:20 Hrs 9937.0 6.01 6 1.0 1.0 1.2 Account of Furnace - I - A Stack Turnel Furnace - I - A Stack 1.5 1.2 1.1/12/23 16:20 Hrs	1//						08/03/24 12:30 Hrs	10030.0	16.05	7	18.0	16.0	NA
GCP-III Stack SMS Furnace 66.5 3.3 Bag Filters 66.5 1.1 1/1/221 16.30 Hrs 9584.0 16.45 5 25.0 16.0 GCP-III Stack Tunnel Furnace 1- A Stack Tunnel Furnace - 1- A Stack Tunnel Furnace - 1 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 Tunnel Furnace - 1 - A Stack Tunnel Furnace 50 1.5 Blower 0.3/10/221 10.20 Hrs 0.4052.0 1.5 0.6 1.0 1.	7	GCP - II Stack	SMS Furnace	70.5	5.5	Bag Filters	02/10/23 12:05 Hrs	10418.0	14.95	6	15.1	12.0	15.0
CCP-III Stack SMS Furnace 66.5 3.3 Bag Filters 101/01/24 12:10 Hrs 10164.0 17.41 14 14.0 18.0 CCP-III Stack SMS Furnace 66.5 3.3 Bag Filters 1001/01/24 15:10 Hrs 10164.0 17.41 14 14.0 18.0 CCP-III Stack SMS Furnace 66.5 3.3 Bag Filters 1001/01/24 15:20 Hrs 9937.0 15.61 12 15.0 11.8 CCP-III Stack Tunnel Furnace 50 1.5 Blower 04/11/23 10:30 Hrs 9758.0 17.0 17.0 13.0 Tunnel Furnace -1- A Stack Tunnel Furnace 50 1.5 Blower 03/03/24 10:00 Hrs 9758.0 6.80 11 17.0 19.0 CANA CAN							10/11/23 12:20 Hrs	9584.0	16.45	. 5	25.0	16.0	22.0
GCP-IIIStack SMS Furnace 66.5 3.3 Bag Filters 01/01/24 17:35 Hrs 9536.0 1741 14 14.0 18.0 18.0 18.0 19.03/24 17:35 Hrs 9536.0 17 4 15.0 16.0 18.0 19.03/24 17:35 Hrs 9536.0 17 4 15.0 11.8 18.0 19.03/24 17:35 Hrs 9536.0 17 4 15.0 11.8 18.0 19.03/24 17:35 Hrs 9536.0 17 4 15.0 11.8 18.0 19.03/24 17:35 Hrs 9536.0 18.5 1 6 18.0 17.0 18.0 19.03 19							11/12/23 14:35 Hrs	9937.0	15.45	4	13.0	16.0	21.0
GCP-IIIStack SMS Furnace 66.5 3.3 Bag Filters 19/03/24 17:35 Hrs 9536.0 17 4 15:0 16.0 11.8 19.00							01/01/24 12:10 Hrs	10164.0	17.41	14	14.0	18.0	20.0
GCP-III Stack SMS Furnace 66.5 3.3 Bag Filters 02/10/23 15:15 Hrs 10418.0 8:76 6 17 4 15.0 11.8 11.8 10418.0 8:76 6 14.0 17.0 17.0 17.0 17.0 17.0 17.0 17.0 17							26/02/24 16:15 Hrs	10183.0	15.61	12	15.0	16.0	4.9
GCP-III Stack SMS Furnace 66.5 3.3 Bag Filters 02/10/23 15:15 Hrs 10418.0 8.76 6 14.0 17.0 Tunnel Furnace - I - A Stack 1.5 Blower 02/10/23 10:00 Hrs 9937.0 6.01 6 11.0 13.0 Tunnel Furnace - I - A Stack 1.5 Blower 03/10/23 10:00 Hrs 6682.0 8.20 10 13.0 18.0 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>19/03/24 17:35 Hrs</td> <td>9536.0</td> <td>17</td> <td>4</td> <td>15.0</td> <td>11.8</td> <td>NA</td>							19/03/24 17:35 Hrs	9536.0	17	4	15.0	11.8	NA
Tunnel Furnace - I - A Stack Tunnel Furnace - So 1.5	3	GCP - III Stack	SMS Furnace	66.5	3.3	Bag Filters	02/10/23 15:15 Hrs	10418.0	8.76	9	14.0	17.0	12.0
Tunnel Furnace - 1 - A Stack Tunnel Furnace 50 1.5 Blower 15/10/24 10:00 Hrs 1030.00 1.50 13.00 1.50 1.							10/11/23 15:23 Hrs	9584.0	8.51	9	18.0	27.0	13.0
Tunnel Furnace - I - A Stack Tunnel Furnace - So II.5 Blower 03/10/24 10:10 Hrs 10183.0 9 6 11.0 13.0	19						11/12/23 16:50 Hrs	9937.0	6.01	9	10.0	12.0	18.0
Tunnel Furnace - I - A Stack							01/01/24 15:26 Hrs	10164.0	8.63	9	11.0	13.0	16.0
Tunnel Furnace - I - A Stack Tunnel Furnace 50 1.5 Blower 03/10/23 10:00 Hrs 6682.0 9 6 NA NA NA Tunnel Furnace - I - A Stack Tunnel Furnace - I - A Stack 50 1.5 Blower 03/10/23 10:00 Hrs 6682.0 8.20 10 13.0 18.0 04/11/23 10:00 Hrs 15/12/23 10:25 Hrs 10658.0 6.80 11 17.0 19.0 02/01/24 10:00 Hrs 8556.0 8.50 9 13.6 8.10 25/02/24 10:00 Hrs 10327.0 7.60 10 26.0 13.00 93/03/24 10:00 Hrs 8441.0 7.90 17.0 17.0 17.0							26/02/24 17:30 Hrs	10183.0	6	9	NA	NA	NA
Tunnel Furnace - I - A Stack Tunnel Furnace 50 1.5 Blower 03/10/23 10:00 Hrs 6682.0 8.20 10 13.0 18.0 15 1 2 2 3 10:25 Hrs 15 1 2 2 3 10:25 Hrs 1658.0 7.60 9 18.0 30.0 15 1 2 2 3 10:25 Hrs 15 10 58.0 6.80 11 17.0 19.0 15 1 2 2 3 10:25 Hrs 10658.0 6.80 11 17.0 19.0 15 1 2 2 3 10:25 Hrs 1052 1 10:00 Hrs 8556.0 8.50 9 13.6 8.10 15 1 2 2 3 10:25 Hrs 10327.0 7.60 10 26.0 13.00 15 1 2 2 3 10:25 Hrs 10327.0 7.60 10 17.0 13.00							08/03/24 10:15 Hrs	10030.0	6	9	NA	NA	NA
9758.0 7.60 9 18.0 30.0 10658.0 6.80 11 17.0 19.0 8556.0 8.50 9 13.6 8.10 10327.0 7.60 10 26.0 13.00 8441.0 7.90 10 17.0 13.00	4	Tunnel Furnace - I - A Stack	Tunnel Furnace	50	1.5	Blower	03/10/23 10:00 Hrs	6682.0	8.20	10	13.0	18.0	21.0
10658.0 6.80 11 17.0 19.0 8556.0 8.50 9 13.6 8.10 10327.0 7.60 10 26.0 13.00 8441.0 7.90 10 17.0 13.00							04/11/23 10:00 Hrs	9758.0	7.60	6	18.0	30.0	18.0
8556.0 8.50 9 13.6 8.10 10327.0 7.60 10 26.0 13.00 8441.0 7.90 10 17.0 13.00					N		15/12/23 10:25 Hrs	10658.0	6.80	11	17.0	19.0	16.0
10327.0 7.60 10 26.0 13.00 8441.0 7.90 10 17.0 13.00							02/01/24 10:00 Hrs	8556.0	8.50	6	13.6	8.10	12.0
8441.0 7.90 10 17.0 13.00							25/02/24 10:00 Hrs	10327.0	09.7	10	26.0	13.00	81
							03/03/24 10:00 Hrs	8441.0	7.90	10	17.0	13.00	NA



Checked By
Dr.Anand Rai
Vice President (HOD-Environment)

9																							_
	8	23.0	24.0	22.1	0.61	12.55	AN	25.0	26.0	19.0	13.6	13.0	AN	24.0	24.0	27.0	23.0	22.0	NA				NA
ng/Nm ³	NOx	16.0	19.0	0.91	12.00	16.00	18.00	21.0	18.0	6.4	18.0	15.0	14.0	26.0	22.0	12.0	21.0	25.0	17.0				50.00
Parameters mg/Nm ³	SO ₂	18.0	14.0	12.0	14.0	17.0	26.0	28.0	16.0	14.0	15.0	14.0	16.0	12.0	18.0	10.0	16.0	17.0	23.0				NA
Para	Particulate Matter (PM)	8	10	8	=	9	9	6	12	6	9	9	∞	4	6	4	4	4	4	222		15/4/2023	<100
Velocity m/sec		06.9	08.9	7.10	02.9	8.20	7.60	7.20	7.20	7.60	7.20	7.80	7	7.80	8.51	09.9	8.50	08.9	7	Shut Down 31/04/2022		In April -	ns
Production fig. of the unit, during	the monitoring period (TPD and MWh)	6682.0	9758.0	10658.0	8556.0	10327.0	8441.0	6682.0	9758.0	10658.0	8556.0	10327.0	8441.0	6682.0	9758.0	10658.0	8556.0	10327.0	8441.0	Shut Dow		Stack dismentled In April - 15/4/2023	CPCB Norms
Date & time of Monitoring		03/10/23 12:15 Hrs	04/11/23 12:18 Hrs	15/12/23 12:28 Hrs	02/01/24 12:10 Hrs	25/02/24 12:30 Hrs	03/03/24 12:00 Hrs	03/10/23 15:05 Hrs	04/11/23 14:35 Hrs	15/12/23 14:42 Hrs	02/01/24 14:23 Hrs	25/02/24 14:00 Hrs	03/03/24 14:15 Hrs	03/10/23 16:50 Hrs	04/11/23 16:22 Hrs	15/12/23 16:10 Hrs	02/01/24 16:10 Hrs	25/02/24 16:30 Hrs	03/03/24 16:45 Hrs				
Pollution Control unit	provided	Blower						Blower						Blower						Blower	Bag Filters		
Diameter of the Stack	(m)	1.5						1.5						1.5						1.8	1.9		
Height of the Stack	(m)	50						50						50							30		
Stack connected to (Name of the Unit)		Tunnel Furnace						Tunnel Furnace						Tunnel Furnace						Boiler	Lime & Coke Handling System		
Name of the Plant and Stack		Tunnel Furnace - I - B Stack						Tunnel Furnace - II - A Stack						Tunnel Furnace - II - B Stack						18 TPH Boiler Stack	De-Dusting System Stack		
Sr.		5		Th	W			9						7						∞	6		

9,																										
2)	93		NA	NA	NA	NA	NA	NA	18.0	24.0	11.0	21.0	22.0	NA	20.0	28.0	11.0	19.0	12.0	NA	NA	NA	NA	NA	NA	NA
mg/Nm ³	NOX		NA	NA	NA	NA	NA	NA	15.0	21.0	12.00	16.0	15.0	18.8	14.00	16.00	12.00	14.00	18.00	15.60	NA	NA	NA	NA	NA	NA
Parameters mg/Nm ³	SO ₂		NA	NA	NA	NA	NA	NA	10.0	12.0	15.0	12.0	0.61	12.6	12.0	18.0	15.0	10.0	23.0	9.61	NA	NA	NA	NA	NA	NA
Pa	Particulate Matter (PM)		15	13	15	16	14	16	15	19	24	23	34	18	22	21	24	21	23	18	6	14	13	14	13	10
Velocity m/sec		ATPA	S	4	S	9	9	4	13.0	12.0	14.5	14.0	16.0	12	12.5	21.5	14.5	13.2	18.9	6	4.5	5.0	6.2	8.9	6.3	5
Production fig. of the unit, during	the monitoring period (TPD and MWh)	Plant Capacity: 0.44 MTPA	300	009	300	288	593	618	294	261	300.0	278	300	287	294.0	300.0	290.0	300.0	325.0	331.0	553.0	456.0	300.0	300.0	625.0	618.0
Date & time of Monitoring		Plant (02/12/23 10:05 Hrs	08/11/23 10:20 Hrs	02/12/23 10:05 Hrs	14/01/24 10:05 Hrs	28/02/24 10:05 Hrs	05/03/24 14:20 Hrs	06/10/23 12:10 Hrs	01/11/23 10:05 Hrs	28/12/23 10:45 Hrs	15/01/24 10:20 Hrs	02/02/24 10:15 Hrs	05/03/24 10:15 Hrs	06/10/23 14:25 Hrs	01/11/23 12:00 Hrs	28/12/23 10:45 Hrs	23/01/24 11:25 Hrs	02/02/24 15:30 Hrs	05/03/24 11:35 Hrs	04/10/23 10:18 Hrs	02/11/23 12:25 Hrs	02/12/23 12:15 Hrs	11/01/24 10:10 Hrs	02/02/24 12:22 Hrs	05/03/24 16:25 Hrs
Pollution Control unit	provided		Bag Filters						Bag Filters						Bag Filters						Bag Filters					
Diameter of the Stack	(m)		0.825						0.914						0.914						0.825					
Height of the Stack	(m)		41.5						48.7						48.7						25.5					
Stack connected to (Name of the Unit)			Lime Stone Hopper						Kiln - I						Kiln - II						Lime Storage Hopper	1				
Name of the Plant and Stack		Lime Calcination Plant	Lime Stone De-dusting	system stack for Kiln I & II					Kiln - I Stack						Kiln - II Stack						Lime De-dusting system	Stack for Kiln I & II				
Sr. No.		=	-				A)		7	ly,	W)				m						4					



0						Ī.		<u> </u>		<u> </u>	_	I_					Ι.			2	0	0	0	0	
,	9	NA	NA	NA	NA	NA	NA	18.0	19.0	18.0	26.0	17.0	NA	NA	NA	NA	NA	NA	NA	26.42	23.00	17.00	26.00	15.00	NA
Parameters mg/Nm ³	NOx	NA	NA	NA	NA	NA	NA	15.00	13.00	16.00	17.00	15.00	19.32	NA	NA	NA	NA	NA	NA	12.00	17.00	13.00	19.00	23.00	14.00
rameters	SO ₂	NA	NA	NA	NA	NA	NA	16.0	18.0	13.0	11.0	26.0	23.2	NA	NA	NA	NA	NA	NA	5.68	21.00	16.00	15.00	14.00	24.00
Pa	Particulate Matter (PM)	12	10	14	12	14	15	11	13	19	20	21	23	15	16	15	12	11	11	15	19	15	20	20	13
weioeny m/sec		3.5	4.1	4.9	5.0	6.2	4	14.0	12.0	15.2	16.0	15.6	13	5.5	4.8	6.2	6.9	7.0	9	14.0	14.0	13.2	16.0	14.0	12
the unit, during	the monitoring period (TPD and MWh)	538	575	575	311	585	585	512	491	575	548	585	585	400	425	575	311	585	585	580	580	584	553	595	290
Date & time of Nontrolling		25/10/23 12:25 Hrs	08/11/23 12:23 Hrs	02/12/23 15:00 Hrs	11/01/24 12:16 Hrs	07/02/24 14:35 Hrs	06/03/24 15:00 Hrs	06/10/23 16:22 Hrs	01/11/23 14:15 Hrs	09/12/23 14:40 Hrs	15/01/24 12:15 Hrs	07/02/24 11:15 Hrs	06/03/24 10:29 Hrs	04/10/23 12:35 Hrs	02/11/23 16:30 Hrs	02/12/23 16:25 Hrs	11/01/24 14:05 Hrs	07/02/24 16:40 Hrs	06/03/24 16:35 Hrs	06/10/23 10:00 Hrs	01/11/23 16:45 Hrs	09/12/23 16:33 Hrs	15/01/24 16:00 Hrs	10/02/24 10:45 Hrs	06/03/24 12:15 Hrs
Control unit	provided	Bag Filters						Bag Filters						Bag Filters						Bag Filters					
the Stack	(m)	1.4						1.3	3					096.0						1.3					
the Stack	(m)	35						09						31						28					
(Name of the Unit)		Lime Stone Hopper						Kiln - III						Lime Storage Hopper						Kiin - IV					
Name of the Flant and Stack		Lime Stone De-dusting	system stack for with III					Kiln - III Stack							dusting system Stack for Kiln III					Kiln - IV Stack					
No.		S	TATE OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NA					9						7						1 1	All I	00			



1 2													
,	00	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
mg/Nm ³	NOx	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Parameters mg/Nm ³	SO ₂	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Pa	Particulate Matter (PM)	10	13	10	14	13	14	13	15	16	15	15	16
Velocity m/sec		4.2	3.8	4.2	4.0	4.8	4	4.2	4.5	5.1	4.2	5.2	9
Production fig. of the unit, during	the monitoring period (TPD and MWh)	899	580	580	553	565	590	495	580	580	553	565	590
Date & time of Monitoring		23/10/23 15:10 Hrs	08/11/23 14:25 Hrs	04/12/23 14:00 Hrs	11/01/24 15:35 Hrs	10/02/24 12:11 Hrs	07/03/24 15:31 Hrs	04/10/23 15:40 Hrs	08/11/23 16:45 Hrs	04/12/23 16:25 Hrs	11/01/24 16:45 Hrs	10/02/24 16:44 Hrs	07/03/24 16:55 Hrs
0	provided	Bag Filters						Bag Filters					
Height of Diameter of the Stack the Stack	(H)	1.4						096'0					
Height of the Stack	(m)	35						31					
Stack connected to (Name of the Unit)		Lime Stone Dedusting	maneda					Lime Dedusting	System				
Sr. Name of the Plant and Stack No.		Lime Stone De-dusting	AT HIM TO WORK HOLDES					Lime De-dusting system	Stack for Miln IV				
Sr. No.		6						10					bi

Ħ	III Sponge Iron Plant					Plant C	Plant Capacity: 2.0 MTPA	ITPA				
1	Flue Gas Ejector Stack	Reformer	40	2.851	I.D Fan	05/10/23 16:45 Hrs	3812.0	38.5	9	12.6	8.1	11.0
						18/11/23 16:50 Hrs	3913.0	40.0	12	25.0	28.0	33.0
						01/12/23 16:45 Hrs	3899.0	38.5	11	16.8	17.6	15.8
45/						25/01/24 16:35 Hrs	4226.0	39.5	13	16.4	6.1	10.6
						04/02/24 10:25 Hrs	3378.0	40.0	10	26.0	28.0	33.0
						14/03/24 16:50 Hrs	4017.0	39	6	31.3	9.4	NA
7	Furnace Dust Collector Stack	Furnace	30	6.0	Cyclone &	05/10/23 10:00 Hrs	3812.0	5.5	13	NA	NA	NA
					Venturi	07/11/23 12:05 Hrs	4026.0	5.8	18	NA	NA	NA
					2000000	01/12/23 10:20 Hrs	3899.0	8.9	19	NA	NA	NA
						25/01/24 12:20 Hrs	4226.0	7.2	91	NA	NA	NA
						15/02/24 15:50 Hrs	4217.0	12.8	19	NA	NA	NA
						14/03/24 11:15 Hrs	4017.0		20	NA	NA	NIA

NA

100

<100

CPCB Norms

Checked By
Dr.Anand Rai
Vice President (HOD-Environment)

-2																			196				34.6		1/27	
	00	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
mg/Nm ³	NOX	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Parameters mg/Nm ³	SO ₂	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	
Pa	Particulate Matter (PM)	17.0	15.0	22.0	18	21	25	16.4	21.0	16.0	20	15	18	19.2	14.5	18.5	16	12	15	12.5	10.5	11.7	-11	10	15	< 50
Velocity m/sec		4.6	4.9	5.6	6.2	4.4	5	5.9	6.1	7.2	9.7	7.9	7	4.3	4.1	5.1	6.0	5.6	5	4.1	5.0	4.8	5.3	4.8	9	ms
Production fig. of the unit, during	the monitoring period (TPD and MWh)	3812.0	3913.0	3899.0	3996.0	3674.0	4017.0	3812.0	3913.0	3899.0	4226.0	3674.0	4018.0	3962	3913	3957	3885	4243	4018	4341	3933	3792	3885	3183	4018	CPCB Norms
Date & time of Monitoring		05/10/23 12:23 Hrs	18/11/23 14:35 Hrs	01/12/23 12:18 Hrs	10/01/24 10:25 Hrs	06/02/24 14:35 Hrs	14/03/24 15:25 Hrs	05/10/23 14:25 Hrs	18/11/23 10:32 Hrs	01/12/23 15:22 Hrs	25/01/24 10:05 Hrs	06/02/24 16:10 Hrs	16/03/24 10:05 Hrs	30/10/23 17:00 Hrs	18/11/23 12:05 Hrs	18/12/23 09:15 Hrs	14/01/24 12:20 Hrs	11/02/24 11:00 Hrs	16/03/24 12:15 Hrs	19/10/23 12:25 Hrs	23/11/23 10:35 Hrs	23/11/23 10:35 Hrs	14/01/24 14:33 Hrs	29/02/24 12:00 Hrs	16/03/24 14:05 Hrs	
Pollution Control unit	provided	Venturi	Scrubber					Cyclone &	Venturi	Sciaboci				Cyclone &	Scrubber					Venturi	Scrubber					
Diameter of the Stack	(m)	6.0						6.0						6.0						6.0						
of ick	(III)	30						30						30						30						
Stack connected to (Name of the Unit)		Prodet screen Area						Product Screen Area						Product Screen Area						Product Silo						
Name of the Plant and Stack		Screen Dust Collector Stack	5004					Screen Dust Collector Stack						Screen Dust Collector Stack	=					Product Silo Dust Collector	Stack					
Sr. No.		3						4					cons	S					48	9						



1										1																
.)	8		NA	NA	NA	NA	NA	0	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	33.0	12.0	24.0	40.0	11.5	NA
ng/Nm ³	NOx		NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	28.0	16.0	21.0	36.0	42.0	123.0
Parameters mg/Nm ³	so ₂		NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	22.0	12.0	18.0	26.0	37.0	8.0
Par	Particulate Matter (PM)		13	15	29	23	24	26	22	25	28	32	33	28	10	16	19	8	12	31	3	5	3	9	9	9
Velocity m/sec		TPA	16.0	15.0	16.2	9.8	6.6	13	7.50	7.80	7.60	8.50	6.02	19	08.9	10.00	7.21	7.42	6.02	10	12.0	13.0	14.5	13.5	14.5	13
Production fig. of the unit, during	the monitoring period (TPD and MWh)	Plant Capacity: 3.5 MTPA	5014.0	8514.0	4624.0	8616.0	5510.0	4618.0	5014	8266	4624	9088	8678	5962	5014.0	8266.0	4624.0	0.9088	8678.0	4618.0	5014.0	8514.0	4624.0	0.9088	1209.0	5427.0
Date & time of Monitoring		Plant	26/10/23 10:00 Hrs	17/11/23 10:20 Hrs	16/12/23 14:23 Hrs	19/01/24 10:35 Hrs	25/02/24 12:00 Hrs	15/03/24 11:25 Hrs	26/10/23 12:10 Hrs	03/11/23 14:35 Hrs	16/12/23 10:10 Hrs	07/01/24 10:15 Hrs	05/02/24 14:00 Hrs	19/03/24 11:30 Hrs	26/10/23 14:30 Hrs	03/11/23 16:50 Hrs	16/12/23 12:25 Hrs	07/01/24 12:35 Hrs	05/02/24 14:00 Hrs	15/03/24 14:15 Hrs	26/10/23 16:42 Hrs	17/11/23 10:20 Hrs	16/12/23 16:30 Hrs	07/01/24 16:45 Hrs	11/02/24 11:45 Hrs	16/03/24 16:25 Hrs
Pollution Control unit	provided		Bag Filters						Bag Filters						Heat	Exchanger					Bag Filters					
Diameter of the Stack	(m)		2.5						2.5						5						5.5					
Height of the Stack	(iii)		45						45						75						45					
Stack connected to (Name of the Unit)			Stock House						Stock House						Blast Furnace Stove						Cast House					
. Name of the Plant and Stack		Blast Furnace Plant	De-Dusting System Stack I						De-Dusting System Stack II						Stove Stack						De-Dusting System Cast	House				
Sr. No.		2	-	Jun M					7						n	Mind					4				0 30	A STATE



1						1								Т
7	93	25.0	28.0	16.0	28.0	21.0	NA	NA	NA	NA	NA	NA	NA	
mg/Nm ³	NOx	12.0	13.0	17.0	17.0	24.0	23.0	NA	NA	NA	NA	NA	NA	
Parameters mg/Nm ³	SO2	18.0	14.0	15.0	15.0	16.0	14.0	NA	NA	NA	NA	NA	NA	
Pa	Particulate Matter (PM)	19	16	16	18	61	17	27	28	33	30	34	32	
Velocity m/sec		5.80	6.20	7.60	7.60	6.50	7	5.6	6.2	7.8	7.8	7.0	∞	
Production fig. of the unit, during	the monitoring period (TPD and MWh)	210.0	82.0	105.0	233.0	5631.0	116.0	0.6088	5648.0	8613.0	8703.0	4319.0	5536.0	
Date & time of Monitoring Production fig. of Velocity the unit, during m/sec		17/10/23 14:30 Hrs	20/11/23 15:30Hrs	25/12/23 15:00 Hrs	03/01/24 10:20 Hrs	28/02/24 12:00 Hrs	27/03/24 16:30 Hrs	17/10/23 16:50 Hrs	20/11/23 10:05Hrs	25/12/23 10:00 Hrs	03/01/24 12:00 Hrs	02/02/24 16:23 Hrs	27/03/24 10:30 Hrs	
Pollution Control unit	provided	Blower						Bag Filters						
Height of Diameter of the Stack the Stack	(m)	1.2						1.7						
Height of the Stack	(III)	59.5						60.5						
Stack connected to (Name of the Unit)		16 TPH Boiler						Coal Injection Unit						
Sr. Name of the Plant and Stack No.		16 TPH Boiler Stack						Coal Injection Plant						
Sr. No.		5						9	ALASS BAZ					

	-											
>	V Sinter Plant -I					· Plant C	Plant Capacity: 2.8 MTPA	ITPA				
-	Fuel Bag Filter Stack	Fuel Raw Material	40	1.804	Bag Filters	10/10/23 10:10 Hrs	7053.0	4.90	17	NA	NA	NA
		Crusning House				09/11/23 10:00 Hrs	8249.0	5.60	17	NA	NA	NA
						12/12/23 11:45 Hrs	7360.0	6.80	16	NA	NA	NA
						09/01/24 10:10 Hrs	7333.0	5.90	18	NA	NA	NA
						14/02/24 10:15 Hrs	4883.0	6.50	19	NA	NA	NA
						11/03/24 10:45 Hrs	7079.0	5.80	25	NA	NA	NA
7	Flux ESP Stack	Raw Material	50	2.404	Electrostatic	10/10/23 12:15 Hrs	7053.0	6.20	19	NA	NA	NA
uq.i		Crushing & Screening House			Precipitators	09/11/23 12:05 Hrs	8249.0	08.9	20	NA	NA	NA
						14/12/23 14:35 Hrs	7252.0	5.80	19	NA	NA	NA
Tip)						09/01/24 12:20 Hrs	7333.0	6.50	21	NA	NA	NA
						14/02/24 12:23 Hrs	4883.0	7.20	23	NA	NA	NA
					- 38	11/03/24 12:05 Hrs	7079.0	7.00	26	NA	NA	NA



Manager (Environment) Preapared By P.P.Nandusekar

-7																		W.	
7	8	NA	NA	NA	NA	NA	NA	38.00	44.00	32.00	33.00	34.00	NA	NA	NA	NA	NA	NA	NA
mg/Nm ³	NOx	NA	NA	NA	NA	NA	NA	29.00	32.00	14.00	26.00	14.00	16.75	NA	NA	NA	NA	NA	NA
Parameters mg/Nm ³	SO ₂	NA	NA	NA	NA	NA	NA	25.00	26.00	15.00	22.00	19.00	19.33	NA	NA	NA	NA	NA	NA
Pa	Particulate Matter (PM)	24	27	30	26	28	29	35	31	32	39	41	40	30	34	36	28	26	33
Velocity m/sec		. 08.9	5.90	5.20	7.20	7.80	7.20	80.6	10.6	9.24	70.6	86.8	8.30	9.65	9.29	10.50	12.24	5.83	8.67
Production fig. of the unit, during	the monitoring period (TPD and MWh)	7053.0	8249.0	7252.0	7333.0	6794.0	7079.0	7441.0	4559.0	7252.0	7368.0	6794.0	7298.0	7441.0	4559.0	7360.0	7368.0	6794.0	5866.0
Date & time of Monitoring Production fig. of the unit, during		10/10/23 15:35 Hrs	09/11/23 15:25 Hrs	14/12/23 10:00 Hrs	09/01/24 15:25 Hrs	03/02/24 14:35 Hrs	11/03/24 14:35 Hrs	20/10/23 16:50 Hrs	02/11/23 10:20 Hrs	14/12/23 12:00 Hrs	22/01/24 10:40 Hrs	03/02/24 11:15 Hrs	07/03/24 11:22 Hrs	20/10/23 15:15 Hrs	02/11/23 14:35 Hrs	12/12/23 15:25 Hrs	22/01/24 16:05 Hrs	03/02/24 16:33 Hrs	23/03/24 10:00 Hrs
Pollution Control unit	provided	Electrostatic	Precipitators					Electrostatic	Precipitators					Electrostatic	Precipitators				
Diameter of the Stack	Œ	2.404						4.200						4.508					
of ck	Œ	20						140						09					
Stack connected to (Name of the Unit)		Propotioning House						Sintering House						Product Sinter Sizing	Discharge End	200			
Name of the Plant and Stack		Propotioning ESP Stack						Main Stack						9/11/1	Discharge Ellu ESF Stack				
Sr. No.		e .						4						2					

VI Sintor Plant II					4	:					
vi Sintel Hallt -II					Plant	Plant Capacity: 2.5 MIPA	TIFA				
1 Main ESP	Sinter Machine	85	5.5	Electrostatic	20/10/23 10:30 Hrs	8452.0	18.2	19	15.0	18.0	24.0
				Precipitators	16/11/23 10:15 Hrs	8862.0	16.7	25	17.0	36.0	42.0
					19/12/23 16:38 Hrs	8305.0	15.8	27	17.0	0.61	25.0
					05/01/24 10:32 Hrs	0.7169	14.5	42.2	16.0	20.0	8.6
					05/02/24 17:45 Hrs	8494.0	14.9	41.2	31.0	23.0	42.0
					26/03/24 11:30 Hrs	8151.0	17.8	32.0	16.2	101	24.0



-7		T																							
1	9	NA	NA	NA	8.6	45.0	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
mg/Nm ³	NOx	NA	NA	NA	20.0	23.0	19.1	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Parameters mg/Nm ³	SO ₂	NA	NA	NA	16.0	31.0	16.2	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
Pa	Particulate Matter (PM)	01	12	15	42	41	32	17	19	17	13	12	14	13	16	12	18	19	16	18	24	61	22	21	23
Velocity m/sec		5.5	6.1	8.9	14.5	14.9	17.8	3.8	4.1	5.8	6.5	0.9	6.2	4.2	5.2	6.2	7.2	5.8	5.0	5.8	6.1	9.9	6.2	5.2	4.3
Production fig. of the unit, during	the monitoring period (TPD and MWh)	8401.0	9057.0	8189.0	0.7199	8494.0	8151.0	8401.0	9057.0	8189.0	8352.0	8333.0	7284.0	8401.0	9057.0	8189.0	8352.0	8333.0	7284.0	8579.0	9057.0	8189.0	7780.0	8333.0	7284.0
Date & time of Monitoring		07/10/23 10:10 Hrs	11/11/23 10:00 Hrs	18/12/23 10:05 Hrs	05/01/24 10:32 Hrs	05/02/24 17:45 Hrs	26/03/24 11:30 Hrs	07/10/23 12:20 Hrs	11/11/23 12:15 Hrs	18/12/23 12:22 Hrs	04/01/24 12:15 Hrs	12/02/24 10:30 Hrs	24/03/24 10:30 Hrs	07/10/23 14:30 Hrs	11/11/23 14:45 Hrs	18/12/23 15:11 Hrs	04/01/24 15:00 Hrs	12/02/24 12:00 Hrs	24/03/24 12:22 Hrs	09/10/23 10:30 Hrs	11/11/23 16:25 Hrs	18/12/23 16:33 Hrs	06/01/24 10:15 Hrs	12/02/24 16:42 Hrs	24/03/24 16:42 Hrs
Pollution Control unit	provided	Bag Filters						Bag Filters						Bag Filters						Bag Filters					
Diameter of the Stack	(m)	4.7						1.4						1.0						6.0					
of	(m)	35						35						29						22					
Stack connected to (Name of the Unit)		Crusher Building						Screen Building						Sinter Product Screen	Building					Sinter Product Crusher	& HLQKF				
Name of the Plant and Stack		Bag Filter- 1 (Flux/Fuel	Crush Or Building					Bag Filter- 2 (Flux/Fuel	Screen building)					Bag Filter- 3(Near Sinter	Froduct Screen Building)					110/0	Product Crusher & HLQKF)				
Sr. No.		7						m						4						S					HV



Manager (Environment)

Preapared By P.P.Nandusekar

Sr. No.	. Name of the Plant and Stack	Stack connected to (Name of the Unit)	Height of the Stack	Diameter of the Stack	Pollution Control unit	Date & time of Monitoring		Velocity m/sec	Pa	Parameters mg/Nm ³	mg/Nm ³	,
			(m)	(m)	provided		the monitoring period (TPD and MWh)		Particulate Matter (PM)	SO ₂	NOx	8
9	Bag Filter- 5 (Near Banker	Banker House & JHO8	32	6.0	Bag Filters	09/10/23 12:05 Hrs	8579.0	4.9	20	NA	NA	NA
	House & Judo)					16/11/23 12:20 Hrs	8862.0	5.7	24	NA	NA	NA
						19/12/23 10:18 Hrs	8305.0	4.3	18	NA	NA	NA
						06/01/24 12:00 Hrs	7780.0	5.8	26	NA	NA	NA
						16/02/24 10:12 Hrs	8910.0	4.5	22	NA	NA	NA
1						25/03/24 10:25 Hrs	8446.0	4.1	26	NA	NA	NA
7	Bag Filter- 6(Banker House)	Banker House	33.5	1.0	Bag Filters	09/10/23 15:15 Hrs	8579.0	3.6	13	NA	NA	NA
1						16/11/23 14:22 Hrs	8862.0	4.2	13	NA	NA	NA
						19/12/23 12:31 Hrs	8305.0	4.0	10	NA	NA	NA
						06/01/24 14:25 Hrs	7780.0	5.0	14	NA	NA	NA
Fig.						16/02/24 12:18 Hrs	8910.0	4.0	12	NA	NA	NA
						25/03/24 12:22 Hrs	8446.0	3.7	12	NA	NA	NA
∞	Bag	Fuel Storage Crusher	33.5	8.0	Bag Filters	27/10/23 14:25 Hrs	8841.0	4.6	12	NA	NA	NA
	Crusher Building)	Building				16/11/23 16:50 Hrs	8862.0	3.9	13	NA	NA	NA
Clark.						19/12/23 14:10 Hrs	8305.0	4.8	14	NA	NA	NA
67						06/01/24 16:40 Hrs	7780.0	4.2	16	NA	NA	NA
						16/02/24 16:50 Hrs	8910.0	5.0	15	NA	NA	NA
						25/03/24 15:38 Hrs	8446.0	4.4	17	NA	NA	NA
IIA	I Captive Power Plant (55 MW)	S MW)										
						27/10/23 11:10 Hrs	53	12.0	2	14.0	13.0	0.81
						05/11/23 11:20 Hrs	54	13.2	3	14.0	17.0	23.0
-	Boiler Stack	Boiler	40	5.0	Blower	23/12/23 16:40 Hrs	54	15.2	4	16.0	18.0	23.0
NA.						08/01/24 16:35 Hrs	54	15.0	4	18.0	12.0	16.0
						11/02/24 15:15 Hrs	54	13.0	4	14.6	18.0	25.0
							Plant shut down	down				
							CPCB Norms	ns	<150	NA	NA	NA



-2			0	0	9	9	3		0	0	0	0	0		
	00		20.0	14.0	20.6	20.6	10.3	NA	26.0	23.0	18.0	18.0	26.0	NA	NA
mg/Nm ³	NOx		15.0	16.0	15.0	15.0	18.0	15.8	0.61	18.0	13.0	12.0	21.0	15.0	NA
Parameters mg/Nm ³	SO ₂		16.0	12.0	12.0	12.0	12.0	12.7	16.0	16.0	16.0	14.0	14.0	14.0	NA
Pa	Particulate Matter (PM)		9	14	17	13	10	12	6	10	7	8	6	9	<50
Velocity m/sec			10.5	6.8	7.8	7.2	8.0	9.7	15.0	13.5	12.2	13.5	16.0	15.4	ms
Production fig. of the unit, during	the monitoring period (TPD and MWh)		365.0	3585.0	1473.0	3218.0	1801.0	2270.0	758.0	3257.0	3872.0	2346.0	3500.0	3460.0	CPCB Norms
Date & time of Monitoring Production fig. of the unit, during			11/10/23 14:35 Hrs	05/11/23 14:25 Hrs	23/12/23 12:25 Hrs	08/01/24 14:25 Hrs	19/02/24 15:45 Hrs	28/03/24 16:42 Hrs	11/10/23 11:25 Hrs	20/11/23 12:05 Hrs	23/12/23 10:15 Hrs	08/01/24 10:40 Hrs	06/02/24 12:00 Hrs	28/03/24 14:30 Hrs	
Pollution Control unit	provided				Fume	system					Rag Filter	Dag i illei			
Height of Diameter of the Stack the Stack	(m)				2.0	ì					3.0	?			
Height of the Stack	(m)				80	3					80	3			
Stack connected to (Name of the Unit)		(1.5 & 1.4 MTPA)			Laddle Heating	Furnace					Reheating Furnace	Sommer Summer			
Sr. Name of the Plant and Stack No.		VIII Billet Caster & Bar Mill (1.5 & 1.4 MTPA)			1 Billet Caster Stack				2		Bar Mill Stack				

IX	IX Coke oven Plant -II				Pl	Plant Capacity: 2.5 MTPA	2.5 MTPA				
					28/10/23 10:25 Hrs	7142.0	10.8	32	112.0	118.0	122.0
				į	05/11/23 16:55Hrs	7137.0	9.01	38	86.0	105.0	123.0
1	Coke Oven Dattery Main	150	11.0	Electrostatic	21/12/23 11:23 Hrs	7140.0	11.2	44	126.0	132.0	144.0
	Stack 1			Precipitators	17/01/24 15:35 Hrs	7127.0	12.0	46	110.0	128.0	133.0
					19/02/24 12:10 Hrs	6210	11.4	45	66	144	158
1					22/03/24 11:30 Hrs	6440	10.1	37	127	131	NA
					11/10/23 10:00 Hrs	6556.0	4.2	9	NA	NA	NA
					06/11/23 10:05 Hrs	7136.0	4.3	8	NA	NA	NA
c	Coke Oven Battery Pushing	30	30	Rag Filters	06/12/23 10:20 Hrs	7403.0	5.2	10	NA	NA	NA
1	Side	3	0:1	Dag i iicis	17/01/24 10:10 Hrs	7127.0	6.2	10	NA	NA	NA
					08/02/24 10:12 Hrs	7043	8.9	6	NA	NA	NA
					01/03/24 10:25 Hrs	6586	9	4	NA	NA	NA

Sr. No.	Name of the Plant and Stack	Stack connected to (Name of the Unit)	Height of the Stack	Diameter of the Stack	Pollution Control unit	Date & time of Monitoring	Production fig. of the unit, during	Velocity m/sec	Par	Parameters mg/Nm ³	ng/Nm ³	-
Sharita.			(m)	(m)	provided		the monitoring period (TPD and MWh)		Particulate Matter (PM)	SO ₂	NOx	8
						11/10/23 11:20 Hrs	6556.0	4.8	4	NA	NA	NA
						06/11/23 12:35 Hrs	7136.0	3.5	10	NA	NA	NA
m	Coke Oven Battery Charging		29.5	1.5	Rag Filters	06/12/23 12:25 Hrs	7403.0	4.9	6	NA	NA	NA
	Side)	eran r Sna	17/01/24 11:45 Hrs	7127.0	5.2	10	NA	NA	NA
						08/02/24 11:45 Hrs	7043	9	10	NA	NA	NA
						01/03/24 12:05 Hrs	9859	5.27	5	NA	NA	NA
						11/10/23 14:35 Hrs	6556.0	3.8	12	NA	NA	NA
W.						06/11/23 16:25 Hrs	7136.0	4.5	14	NA	NA	NA
4	4 Coal Crushing		19.5	1.5	Bao Filters	07/12/23 15:45 Hrs	7425.0	5.5	16	NA	NA	NA
1/1/	0			2	ciam r San	16//01/24 10:25 Hrs	7119.0	6.2	61	NA	NA	NA
						09/02/24 16:22 Hrs	7166.0	4.5	18	NA	NA	NA
						04/03/24 10:30 Hrs	6503.0	5.2	16	NA	NA	NA
W						09/10/23 09:50 Hrs	6573.0	4.0	12	NA	NA	NA
						07/11/23 10:35 Hrs	6913.0	5.0	16	NA	NA	NA
5	5 Coke Cutting		25	8-	Bao Filtere	07/12/23 10:15 Hrs	7425.0	6.2	15	NA	NA	NA
W	0				Grann r Smor	16//01/24 12:04 Hrs	7119.0	5.8	17	NA	NA	NA
W						09/02/24 14:35 Hrs	7166.0	5.0	91	NA	NA	NA
						04/03/24 15:25 Hrs	6503.0	4.2	13	NA	NA	NA
						11/10/23 15:50 Hrs	6556.0	5.1	15	NA	NA	NA
K#						07/11/23 16:25 Hrs	6913.0	8.9	14	NA	NA	NA
9	6 Coke Bunker		30	25	Bao Filters	06/12/23 15:10 Hrs	7403.0	8.1	17	NA	NA	NA
			2	ì	eran r San	16//01/24 14:32 Hrs	7119.0	7.2	20	NA	NA	NA
W						08/02/24 14:33 Hrs	7043.0	7.0	21	NA	NA	NA
						04/03/24 12:20 Hrs	6503.0	0.9	18	NA	NA	NA
						17/10/23 12:00 Hrs	354.0	7.5	16	0.91	12.0	26.0
						13/11/23 12:45 Hrs	117.0	6.9	19	16.0	14.0	28.0
7	7 Boiler		30	10		05/12/23 12:00 Hrs	307.0	8.6	18	12.0	13.0	16.0
l di						03/01/24 14:28 Hrs	335.0	7.8	15	16.0	12.0	20.0
						28/02/24 14:05 Hrs	317.0	8.0	91	15.0	18.0	22.0
				0.00		18/03/24 14:30 Hrs	265.0	7.1	15	10.0	15.0	NA



Sr. No.	Sr. Name of the Plant and Stack No.	Stack connected to (Name of the Unit)	Height of the Stack	Height of Diameter of the Stack the Stack	Pollution Control unit	Date & time of Monitoring Production fig. of Velocity the unit, during m/sec	Production fig. of the unit, during	Velocity m/sec	Pa	Parameters mg/Nm ³	mg/Nm ³	
			(m)	(II)	provided		the monitoring period (TPD and MWh)		Particulate Matter (PM)	SO_2	NOx	00
17						28/10/23 16:00 Hrs	7142.0	8.2	25	0.911	123.0	133.0
						22/11/23 15:15 Hrs	7081.0	8.6	35	145.0	124.0	0.881
-	Coke Oven Battery Main Stack		150	11.04	Natural Deaft	20/12/23 16:18 Hrs	7168.0	10.0	32	120.0	142.0	138.0
	(C &D)		001	11:01	Natural Diant	13/01/24 16:35 Hrs	7070.0	12.0	38	119.0	112.0	128.0
						27/02/24 15:45 Hrs	6409.0	11.8	35	215.0	126.0	132.0
						21/03/24 11:20 Hrs	6260.0	12.5	33	122.0	119.0	NA
						28/10/23 10:00 Hrs	7142.0	5.2	9	NA	NA	NA
						22/11/23 10:05 Hrs	7081.0	4.2	7	NA	NA	NA
0	Coke Oven Battery Pushing		30	8 6	Rag Filters	20/12/23 10:22 Hrs	7168.0	5.6	8	NA	NA	NA
	Side		2	0.4	Dag I IIICIS	13/01/24 10:00 Hrs	7070.0	6.2	10	NA	NA	NA
						27/02/24 11:38 Hrs	6409.0	7.2	8	NA	NA	NA
						02/03/24 10:10 Hrs	6597.0	6.5	12	NA	NA	NA
						28/10/23 12:10 Hrs	7142.0	4.5	4	NA	NA	NA
						22/11/23 11:55 Hrs	7081.0	3.5	10	NA	NA	NA
c	Coke Oven Battery Charging		205	١.	Rag Filters	20/12/23 12:00 Hrs	7168.0	4.8	11	NA	NA	NA
	Side			<u>;</u>	Dag i ilicis	13/01/24 12:10 Hrs	7070.0	5.0	12	NA	NA	NA
						27/02/24 10:15 Hrs	6409.0	8.9	10	NA	NA	NA
M						02/03/24 11:45 Hrs	6597.0	8.9	11	NA	NA	NA

